

SpectroVisc Q3000 Series

PORTABLE KINEMATIC VISCOMETERS

Solvent-free, simple to use, fast and accurate results



Applications include:

- **Machine Condition Monitoring**
Increase availability of critical equipment by monitoring viscosity changes due to oil degradation and contamination. Avoid inadequate lubrication which causes adhesive wear in machinery and is a principal cause of equipment downtime.
- **Quality Control for Fuel/Oil Production and Blending**
- **Incoming Inspection Quality Control**

High accuracy 40C kinematic viscosity measurements for new and in-service oils

Lab-quality results when and where you need them

- Accuracy +/- 3% Relative Standard Deviation to NIST viscosity standards.
- User Correction feature allow in-house validation to viscosity standards.

Solvent-free operation

- Fewer consumables, lower disposal costs and less environmental impact.
- Easy cleaning with the patented split-cell design – just wipe off the surfaces with a nonabrasive cleaning pad between samples.

Requires only a few drops of oil to test

- Obtain samples without impacting lubricant level; only a few drops (60 μ L) of oil required. A positive displacement pipette is provided for the most precise, repeatable measurements.

Expanded I/O capability

- Import sample lists and export measurement results via ViscTrack or AMS Oilview software.

Test even dark and sooty samples


- Innovative design allows testing of virtually any sample including dark and sooty or transparent samples without any pre-checks.

Fast and easy to use

- Test results in only a few minutes for direct measurement of kinematic viscosity.
- Full-color touchscreen display guides the operator through testing, and supports multiple languages.
- Self-contained unit without thermometers, density checks or other preparation needed. Simply insert the sample and read results.

Portable, battery-powered design

- Fits easily into a toolbox or carrying bag and capable of operation for over six hours before recharge.



Positive Displacement Pipette

SpectroVisc Q3000 Series Ordering Information

The SpectroVisc Q3050 includes the base viscometer, battery charger, USB cable, user's manual DVD and ViscTrack software. The recommended Q3050 Standard Accessories Kit SA1021 includes a positive displacement pipette, disposable pipette tips and cleaning pads for 192 samples, and two viscosity standards. The SpectroVisc Q3050 can also be ordered as a combination kit with the FluidScan® Q1000 or Q1100 portable infrared fluid condition monitors.

The recommended Q3000 Standard Accessories Kit SA1002 includes disposable 60 µl pipettes and cleaning pads for 100 samples, and two viscosity standards.

PART NUMBER	
SpectroVisc-Q3050	SpectroVisc Q3050 Portable Viscometer, 1-700 cSt. Requires SA1021 Standard Accessories Kit.
SpectroVisc-Q3000	SpectroVisc Q3000 Portable Viscometer, 10-350 cSt. Requires SA1002 Standard Accessories Kit.
Spectro-Q1100/Q3050	FluidScan Q1100 Lubricant Condition Monitor & SpectroVisc Q3050 Combo Kit. Requires SA1022 Standard Accessories for Combo Kit.
Spectro-Q1000/Q3050	FluidScan Q1000 Lubricant Condition Monitor & SpectroVisc Q3050 Combo Kit. Requires SA1022 Standard Accessories for Combo Kit.

PRODUCT INFORMATION	
Applications	Lubricant oils (mineral and synthetic), coolants, glycol, and any Newtonian fluid within the measuring range
Output	Kinematic Viscosity (cSt) @ 40°C V100 viscosity calculation from VI index input (Q3050 only)
Methodology	ASTM D 7279 modified, ASTM D 445 modified
Standard Analytical Range	Q3000: 10-350 cSt @ 40°C Q3050: 1-700 cSt @ 40°C
Accuracy	Q3000: ≤ ± 3% of measured value over range 10-350 cSt Q3050: ≤ ± 3% of measured value over range 1-350 cSt ≤ ± 5% of measured value for viscosity > 350 cSt <i>Accuracy specification is with use of user correction function.</i>
Repeatability	Q3000: ≤ ± 3% RSD of measured value, typical Q3050: ≤ ± 3% RSD of value, typical, over range 1-350 cSt ≤ ± 5% RSD of measured value for viscosity > 350 cSt <i>RSD is Relative Standard Deviation.</i>
Test Temperature Control	± 0.1°C
Calibration	Not Required

OPERATIONAL SPECIFICATIONS	
Sample Volume	60µL (about 3-4 drops)
Solvents/Reagents	None
Ambient Operating Temperature	0°C to 40°C (32°F to 104°F)
Relative Humidity	10% to 80% r.h. non-condensing
Ambient Altitude	Up to 5,000 meters (16,404 feet)

USER INTERFACE SPECIFICATIONS	
Display	Fixed Angle Color Touchscreen Display
Data Transfer	USB for software updates
Data Entry	Touchscreen

POWER REQUIREMENTS	
Battery Power Source	Built in Rechargeable Lithium Ion Battery
Power	AC 110/240 V, 50/60 Hz, 10 Watts
Typical Runtime	6-8 hours with full charge
Recharge Time	2.5 hrs

MECHANICAL SPECIFICATIONS	
Dimensions	152 mm (H) x 127 mm (W) x 203 mm (D) (6.0 in x 5.0 in x 8.0 in)
Weight	1.8 kg (4.0 lbs)
Shipping Package Dimensions	7.9 cm (H) x 6.3 cm (W) x 5.5 cm (L) (20 in x 16 in x 14 in)
Shipping Package Weight	4.9 kg (11 lbs)

COMPLIANCE	
CE Mark: EMC Directive (2004/108/EC); RoHS	

CONSUMABLES	
P-11177	Positive displacement pipette, 10-100 µL
P-11178	Pipette tips for P-11177, package of 192
P-11201	Pipette tips for P-11177, package of 960
PV1011	Disposable non-abrasive cleaning pads, package of 500
P-11052	60 µL disposable pipettes, package of 500
PV1025	Visc 30 standard, 20 ml
PV1026	Visc 120 standard, 20 ml



Combination Kit includes a FluidScan Q1000 Series infrared fluid condition monitor and a SpectroVisc Q3050 portable kinematic viscometer.